Tramper S-335

Fully automatic tray sealing machine

General description

The Tramper S-335 is a small, servo-driven tray sealing machine that enables to package your products in a professional manner. With a seal range of 350 x 300 mm, the S-335 offers the ideal solution for small and medium volume productions. This tray sealing machine is suitable for single-line applications.

Tramper Technology

- Suitable for the tray sealing of products in liquid and solid form
- Prepared for Modified Atmosphere Packaging
- Extremely simple conversion between different tray sizes

Automatic denesting

Easy changeover!

Tramper S-335

The sealing machine is equipped with servo-controlled drives, allowing both solid and fluid products to be packaged.

The S-335 has a compact and robust construction and combines these properties with a high sealing quality. The machine is known for its simple control and excellent accessibility. For rapid conversion, the sealing machine is fitted with lightweight moulds that can be manually changed.

For fully automated processing, the S-335 can be equipped with a tray denester, type Tramper D-360, with a filling system, type Tramper F-360 and/or a lidding machine, type Tramper D-360.

This tray sealing machine is very suitable as a base model for products with growth potential!

Simple controls

Lightweight moulds

Technical specifications

Machine dimensions	1700 mm x 950 mm x 2000 mm (lxwxh = without input conveyor)
Length input conveyor	standard 2200 mm, extension in sections of 400 mm possible
Height input conveyor	980 mm, ± 50 mm
Seal range	350 mm x 300 mm x 130 mm (lxwxh)
Maximum film width	360 mm
Thickness of film	25 to 160 µm
Diameter of film core	76 mm
Packaging conditions	prepared for packaging with vacuum or gas (MAP)
Electrical connection	400 VAC, 32 Amp
Power	3 kW
Compressed air usage	± 15 litres per cycle (depending on the options)
Capacity	up to 18 cycles per minute

Our partner:

Food Automation
ENGINEERED FOR EXCELLENCE IN MACHINERY

Food Automation Pty Ltd
PO Box 3242 • Newton 5074, South Australia
M: +61 4 27 56 56 58
E: chris@foodautomation.com.au
www.foodautomation.com.au

Tramper Technology

www.trampertechnology.nl