

# Tramper S-460

Fully automatic tray sealing machine



Extra film unwinder  
(option)

## General description

The Tramper S-460 is a servo-driven tray sealing machine that enables you to package your products in a professional manner. The S-460 is with a seal range of 600 x 400 mm suitable for single-line and two-line sealing applications.



- ▶ Suitable for the tray sealing of products in liquid and solid form
- ▶ Prepared for Modified Atmosphere Packaging
- ▶ Extremely simple conversion between different tray sizes



Automatic denesting



Easy changeover!

## Tramper S-460

The sealing machine is equipped with a servo-controlled drive, allowing both solid and fluid products to be packaged.

The S-460 is constructed in a robust and accessible way. The sealing machine has a very high-quality finishing, which more than meets the demanding hygienic standards in the food industry. All these qualities together contribute to a perfectly sealed end product. The S-460 is fitted with changeable moulds, which can be changed quickly and easily with the aid of a mobile unit for the format parts.

For fully automated processing, the sealing machine can be modularly extended with one or more tray denesters, filling systems and lidding machines. It is also possible to equip this machine with a tailor made product feeding system.



Simple controls



Filling system

### Technical specifications

Machine dimensions	2750 mm x 1150 mm x 2100 mm (lxwxh = without input conveyor)
Length input conveyor	standard 3000 mm, extension in sections of 650 mm possible
Height input conveyor	980 mm, ± 50 mm
Seal range	600 mm x 400 mm x 130 mm (lxwxh)
Maximum film width	560 mm
Thickness of film	25 to 160 µm
Diameter of film core	76 mm
Packaging conditions	prepared for packaging with vacuum or gas
Electrical connection	400 VAC, 32 Amp
Power	8 kW
Compressed air usage	± 15 litres per cycle (dependent on the options)
Capacity	up to 15 cycles per minute

Our partner:



**Food Automation**  
ENGINEERED FOR EXCELLENCE IN MACHINERY

**Food Automation Pty Ltd**

PO Box 3242 • Newton 5074, South Australia

M: +61 4 27 56 56 58

E: [chris@foodautomation.com.au](mailto:chris@foodautomation.com.au)

[www.foodautomation.com.au](http://www.foodautomation.com.au)



[www.trampertechnology.nl](http://www.trampertechnology.nl)