

CARTON CLOSING MACHINE C30



- COMPACT
- SPEED UP TO 35 CARTONS PER MINUTE
- EASY TO USE AND MAINTAIN
- EASY SIZE CHANGE OVERS
- SUITABLE FOR DUPLEX AND CORRUGATED BOARD



SCHUT SYSTEMS bv

Loubergweg 22
NL 6961 EK Eerbeek

T +31 (0)313 674 500
F +31 (0)313 674 550
E info@schutsystems.com

Food Automation Pty Ltd
PO Box 3242 Newton
South Australia 5074
T: +61 427 565 658
E: chris@foodautomation.com.au
W: www.foodautomation.com.au

schutsystems.com



CARTON CLOSING MACHINE C30

The **C30 three flap carton closing machine** is a continuously operating, compact closer, working in an angle. The machine can be placed in line with for example the F30 or F111 carton erecting machine.

The C30 is a flexible machine that can easily be adapted to your demands. Care has been taken regarding reliability, easy access for operators, maintenance and service. The machine is equipped with a Nordson glue unit. The manuals are extensive and all essential machine parts are numbered.

Photo above

The flexible over belt system can handle overfilled cartons.

Photo upper left side

Quick size change overs reduce the change over time.

TECHNICAL CHARACTERISTICS

Speed	Up to 35 cartons p/min (Question to carton size and carton construction)
Supply voltage	400V, 3 phase, Pe + neutral
Control voltage	24V DC
Power demand	6 kW
Directive	Low Voltage (LVD) (2014/35/EC) EMC Directive (2014/30/EC) Machinery Directive (MD) (2006/42/EC)
Air pressure	6 bar dry and filtered
Air consumption	40 NI/min at 6 bar
Machine size	2410 x 1875 x 1410 mm
Weight	650 kg
Options	Frequency controller Product coding unit Mirrow turned Automatic Nordson glue loading system

Other options on request

